Product Type microSDXC Memory Card	Family Line EVO PLUS
Application Mobile phone, Smartphone, Tablet, etc	Capacity 128GB (1GB=1Billi may be lower than storage may be use control purposes.
Interface	Dimension (WxHx
UHS-I, compatible to UHS interface	15x11x1 mm
Weight	Accessory
Approx. 0.25g	SD adapter
Speed Read : up to 160MB/s Write : Lower than Read Speed* Read/Write speed requires compatible devices capable of reaching such speeds and it may vary among different host devices and testing conditions. * For products incompatible with UHS-I interface, the speeds may vary subject to different interface conditions	Speed Class U3, V30, A2
Operating Voltage 2.7~3.6V	Storage Temperat -40°C to 85°C
Operating Temperature -25°C to 85°C	Humidity -
Durability 10,000 mating cycles	
EMC CE(UKCA)/FCC/VCCI/RCM	
Limited 10 year warranty. * Warranty does not extend to dashcam, CCTV, surveillance camera and other write- intensive uses. * Warranty for SD adapter is limited to 1 year.	
	microSDXC Memory Card Application Mobile phone, Smartphone, Tablet, etc Interface UHS-1, compatible to UHS interface Weight Approx. 0.25g Read: up to 160MB/s Write : Lower than Read Speed* Read: up to 160MB/s Write : Lower than Read Speed* Read: up to 160MB/s Write : Lower than Read Speed* Read: up to 160MB/s Write : Lower than Read Speed* Read/Write speed requires compatible devices capable of reaching such speeds and it may vary among different host devices and testing conditions. * For products incompatible with UHS-1 interface, the speeds may vary subject to different interface conditions Operating Voltage 2.7~3.6V Derating Temperature -25°C to 85°C Durability 10,000 mating cycles EMC CE(UKCA)/FCC/VCCI/RCM Limited 10 year warranty. * Warranty does not extend to dashcam, CCTV, surveillance camera and other write- intensive uses. * Warranty for SD adapter is limited to 1